



nLighten edge data center

Munich.

MUC1

Nicknamed Germany's Silicon Valley, Munich is home to a vast range of technology companies as well as automotive, other manufacturing and creative industries. Munich is also one of the most attractive business locations in Germany, not least due to its excellent quality of life. The nLighten data center is proud to support Munich businesses with its multi-megawatt green IT platform.



nLighten München.


Robert-Bosch-Straße 12
85748 Garching bei München

Location specifics.

The data center is conveniently located just off the A9/A99 ring road, 15 minutes from the main train station, and 20 minutes by car from Munich International Airport. The data center has an area of 2,500 m², 2,400 kW of power, an office area and ample parking space.

Like the other nLighten facilities, the Munich location enables our customers to benefit from a well-connected, high-availability data center and capable of housing high-density cabinets. The data center comes with a wide range of on-site services and a growing ecosystem of partners, all there to optimally support our customers' IT environment.

Highlights.



2,500 m²

of edge data center space



2,400 kW

proposed end-state site capacity



AI-readiness:
Design build of up to 50+ kW rear-door cooling








Sustainability:
Commitment to a net-zero carbon footprint



Compliance:
ISO27001 in all locations

Edge data center Munich Features.

 close · coupled · connected DATA CENTER	<table border="1"> <tbody> <tr> <td>Location</td> <td>Conveniently located for easy access by road and public transport</td> <td>✓</td> </tr> <tr> <td>Design</td> <td>Tier III design target</td> <td>✓</td> </tr> <tr> <td>Connectivity</td> <td>Carrier-neutral data center with diverse fibre entry points and meet-me areas</td> <td>✓</td> </tr> <tr> <td>Cooling</td> <td>Cooling and humidity design complying with ASHRAE A1 allowable category</td> <td>✓</td> </tr> <tr> <td>Compliance</td> <td>ISO27001, and programme in place for PCI-DSS, SOC1, SOC2, ISO14001, ISO 50001, ISO22301</td> <td>✓</td> </tr> </tbody> </table>	Location	Conveniently located for easy access by road and public transport	✓	Design	Tier III design target	✓	Connectivity	Carrier-neutral data center with diverse fibre entry points and meet-me areas	✓	Cooling	Cooling and humidity design complying with ASHRAE A1 allowable category	✓	Compliance	ISO27001, and programme in place for PCI-DSS, SOC1, SOC2, ISO14001, ISO 50001, ISO22301	✓	
Location	Conveniently located for easy access by road and public transport	✓															
Design	Tier III design target	✓															
Connectivity	Carrier-neutral data center with diverse fibre entry points and meet-me areas	✓															
Cooling	Cooling and humidity design complying with ASHRAE A1 allowable category	✓															
Compliance	ISO27001, and programme in place for PCI-DSS, SOC1, SOC2, ISO14001, ISO 50001, ISO22301	✓															
 POWER	<table border="1"> <tbody> <tr> <td>Redundant power with independent A and B feeds to each cabinet</td> <td>✓</td> </tr> <tr> <td>Proposed end-state site capacity</td> <td>2,400 kW</td> </tr> <tr> <td>Design power usage effectiveness (PUE) all phases</td> <td>1.29</td> </tr> <tr> <td>Standard density</td> <td>2 – 7 kW available</td> </tr> <tr> <td>High density positions up to 12 kW Air-cooling and 50+ kW rear door-cooling (AI-ready)</td> <td>Phase 2</td> </tr> </tbody> </table>	Redundant power with independent A and B feeds to each cabinet	✓	Proposed end-state site capacity	2,400 kW	Design power usage effectiveness (PUE) all phases	1.29	Standard density	2 – 7 kW available	High density positions up to 12 kW Air-cooling and 50+ kW rear door-cooling (AI-ready)	Phase 2						
Redundant power with independent A and B feeds to each cabinet	✓																
Proposed end-state site capacity	2,400 kW																
Design power usage effectiveness (PUE) all phases	1.29																
Standard density	2 – 7 kW available																
High density positions up to 12 kW Air-cooling and 50+ kW rear door-cooling (AI-ready)	Phase 2																
 SUSTAINABILITY	<table border="1"> <tbody> <tr> <td>Heat recovery; residual redirected to local heating networks</td> <td>Feasibility study</td> </tr> <tr> <td>Commitment to a carbon-free energy footprint</td> <td>Green certificates upon request, CFE scoring commitment</td> </tr> </tbody> </table>	Heat recovery; residual redirected to local heating networks	Feasibility study	Commitment to a carbon-free energy footprint	Green certificates upon request, CFE scoring commitment												
Heat recovery; residual redirected to local heating networks	Feasibility study																
Commitment to a carbon-free energy footprint	Green certificates upon request, CFE scoring commitment																
 SECURITY	<table border="1"> <tbody> <tr> <td>Dual factor access control (pin / biometrics); five lines of defence design target</td> <td>✓</td> </tr> <tr> <td>CCTV – Full coverage, storage in compliance with local laws</td> <td>✓</td> </tr> <tr> <td>Fire suppression in the data hall</td> <td>✓</td> </tr> </tbody> </table>	Dual factor access control (pin / biometrics); five lines of defence design target	✓	CCTV – Full coverage, storage in compliance with local laws	✓	Fire suppression in the data hall	✓										
Dual factor access control (pin / biometrics); five lines of defence design target	✓																
CCTV – Full coverage, storage in compliance with local laws	✓																
Fire suppression in the data hall	✓																
 SUPPORT	<table border="1"> <tbody> <tr> <td>24/7 service desk and 24/7 access to NOC services</td> <td>✓</td> </tr> <tr> <td>24/7 remote hands</td> <td>✓</td> </tr> <tr> <td>On-site staffing</td> <td>Office hours</td> </tr> </tbody> </table>	24/7 service desk and 24/7 access to NOC services	✓	24/7 remote hands	✓	On-site staffing	Office hours										
24/7 service desk and 24/7 access to NOC services	✓																
24/7 remote hands	✓																
On-site staffing	Office hours																