

close · coupled · connected





Its diverse economy, spanning manufacturing and research, is forging Bridgend into a technology and business center, promoting innovation and high-tech industries. The nLighten data center in Bridgend reinforces the city's status as a key regional industrial and educational hub in Wales, supporting local businesses with cutting-edge IT infrastructure and solidifying Bridgend's role in the region's growth and innovation.



nLighten Bridgend.

Unit 3, Bridgend Science Park Technology Drive CF31 3NA Bridgend

Location specifics.

The data center is conveniently located in the south of Bridgend, close to the M4 motorway between Cardiff and Swansea. The data center has an area of 1,100 m², 1,500 kW of power, an office area and ample parking space.

Like the other nLighten facilities, the Bridgend location enables our customers to benefit from a well-connected, high-availability data center and capable of housing high-density cabinets. The data center comes with a wide range of on-site services and a growing ecosystem of partners, all there to optimally support our customers' IT environment.

Highlights.





1,500 kW

proposed end-state site capacity



Al-readiness:
Design build of up to 50+ kW
rear-door cooling



Sustainability:
Commitment to a net-zero
carbon footprint



Compliance:
ISO27001
Explore our certifications

Edge data center Bridgend Features.



	Location	Conveniently located for easy access by road and public transport	~
	Design	 Tier III design target	
nlighten	Connectivity	Carrier-neutral data center with diverse fibre entry points and meet-me areas	
DATA CENTER	Cooling	Cooling and humidity design complying with ASHRAE A1 allowable category	
	Compliance	ISO27001 We adhere to industry-leading standards, comply with applicable regulations, and continuously enhance our infrastructure and security posture. Explore our certifications	▽
	Redundant power with independent A and B feeds to each cabinet		▽
	Proposed end-state site capacity		1,500 kW
	Design power usage effectiveness (PUE) all phases		1.29
	Standard dens	ity	2 – 7 kW available
POWER	High density p	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready)	2 – 7 kW available New rooms
	High density p 50+ kW rear density P Heat recovery,	ositions up to 12 kW Air-cooling and	New rooms Feasibility study
POWER	High density p 50+ kW rear density p Commitment of the second sec	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of	Feasibility study Green certificates upon request, CFE scoring
JSTAINABILITY	High density p 50+ kW rear density p 50+ kW rear density p Commitment of the second se	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of n target overage, storage in compliance with local laws	Feasibility study Green certificates upon request, CFE scoring commitment
JISTAINABILITY	High density p 50+ kW rear density p 50+ kW rear density p Commitment of the second se	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of n target overage, storage in compliance with local laws on in the data hall esk and 24/7 access to NOC services	Feasibility study Green certificates upon request, CFE scoring commitment